

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) A ~~D~~drive system for regulating devices in motor vehicles with a housing in which a drive element of the regulating device, a disc armature motor with an armature disc and a planet wheel transmission are arranged which has a hollow wheel with internal toothing fixed on the housing, an output internal geared wheel connected to the drive element of the regulating device, and a radially flexible ring whose external toothing meshes partially with the internal toothing of the hollow wheel fixed on the housing and of the output hollow wheel and whose inner sleeve face rolls on rollers which are mounted on a drive hub connected to the armature disc,
~~characterised in that wherein~~
a journal (50) of the output internal geared wheel (5) extending over a significant part of the length of a fixed drive axle (40) is centred between the fixed drive axle (40) and a drive hub cylinder (60) of the drive hub (6).
2. (Currently amended) The ~~D~~drive system according to claim 1, ~~characterised in that wherein~~ the length of the drive hub cylinder (60) corresponds substantially to the height of the rollers (71, 782).
3. (Currently amended) The ~~D~~drive system according to claim 1 ~~or 2~~, ~~characterised in that wherein~~ the fixed drive axle (40) is connected to a first housing cover (41) of the housing and is supported on a second housing cover (42) of the housing.
4. (Currently amended) The ~~D~~drive system according to ~~at least one of the preceding claims claim 1~~, ~~characterised in that wherein~~ the fixed drive axle (40) and the drive hub cylinder (60) are made from one of steel ~~or~~ and a steel alloy and the journal (50) centred between the fixed drive axle (40) and the drive hub cylinder (60) is made from sintered metal.

5. (Currently amended) ~~The Ddrive system according to at least one of the preceding claims claim 1, characterised in that~~ wherein the hollow wheel (20) fixed on the housing is connected to a base disc (2) ~~or~~ and is formed as a part of a base disc (2) which supports permanent magnets (32) of the disc armature motor (3) and has centring elements (91, 92) which are arranged on the periphery and centre at least one of the two housing covers (41) relative to the base disc (2).
6. (Currently amended) ~~The Ddrive system according to claim 5, characterised in that~~ wherein socket areas are worked into the outwardly aligned edge of the hollow wheel (20) fixed on the housing and are adapted at least in sections to the contour of the permanent magnets (32) of the disc armature motor (3).
7. (Currently amended) ~~The Ddrive system according to claim 5 or 6, characterised in that~~ wherein the socket areas are formed in the outwardly directed edge of the hollow wheel (20) fixed on the housing as radially outwardly opening sockets.
8. (Currently amended) ~~The Ddrive system according to one of the preceding claims 5 to 7, characterised in that~~ wherein the internal toothing (21) of the hollow wheel (20) fixed on the housing is formed in a metal edge of the base disc (2).
9. (Currently amended) ~~The Ddrive system according to at least one of the preceding claims 5 to 8, characterised in that~~ wherein the centring elements (91, 92) of the base disc (2) correspond to counter centring elements (93, 94) of the first housing cover (41) which support the fixed drive axle (40).
10. (Currently amended) ~~The Ddrive system according to at least one of the preceding claims 5 to 9, characterised in that~~ wherein the base disc (2) has a cropped peripheral edge (22)
11. (Currently amended) ~~The Ddrive system according to at least one of the preceding claims 5 to 10, characterised in that~~ wherein the base disc (2) has profiling for positioning ~~or~~ and securing the position of the permanent magnets (32).

12. (Currently amended) ~~The Ddrive system according to at least one of the preceding claims 5 to 10, characterised in that~~ wherein the base disc (2) is connected through stamped indentations and/or cropped bracket plates to a disc ~~preferably~~ of plastics supporting the permanent magnets (32).

13. (Currently amended) ~~The Ddrive system according to one of the preceding claims 5 to 12, characterised in that~~ wherein the base disc (2) is made of plastics in which socket areas are formed which are adapted at least in sections to the contour of the permanent magnets (32) of the disc armature motor (3).

14. (Currently amended) ~~The Ddrive system according to one of the preceding claims 5 to 12, characterised in that~~ wherein the base disc (2) consists of plastics in which the permanent magnets (32) of the disc armature motor (3) are cast.

15. (Currently amended) ~~The Ddrive system according to at least one of the preceding claims 5 to 14, characterised in that~~ wherein the socket areas of the base disc (2) are made from bracket plates which are stamped out ~~or~~ and bent round from the base disc (2).

16. (Currently amended) ~~The Ddrive system according to at least one of the preceding claims 5 to 14, characterised in that~~ wherein the socket areas of the hollow wheel (20) fixed on one of the housing ~~or~~ and of the base disc (2) surround the permanent magnets (32) so far that a defined position of the permanent magnets (32) is ensured.

17. (Currently amended) ~~The Ddrive system according to one of the preceding claims~~ claim 1, characterised in that wherein the ferrite metal parts of the drive system are thickened up by tailored blanks only in the region of the flux-conveying short circuits.

18. (Currently amended) ~~The Ddrive system according to at least one of the preceding claims~~ claim 1, characterised in that wherein the drive hub (6) is made from one of a steel stamped part, a sintered metal, ~~and/or~~ a glass-fibre ~~or~~ and carbon-fibre reinforced plastics.

Docket No.: 56676/M521
Amdt date February 17, 2006

19. (Currently amended) The Ddrive system according to claim 18, ~~characterised in that~~ wherein the drive hub ~~(6)~~ has several cropped angles ~~(63)~~ formed out from the surface.
20. (Currently amended) The Ddrive system according to claim 18 ~~or 19~~, ~~characterised in that~~ wherein one of the drive hub cylinder ~~(60)~~ and ~~or~~ the roller bearings ~~(61, 62)~~ are designed as passages through the drive hub ~~(67)~~.
21. (Currently amended) The Ddrive system according to claim 20, ~~characterised in that~~ wherein the outer cylindrical surface of the passages is supported by hardened steel bushes with collar.
22. (Currently amended) The Ddrive system according to claim 20 ~~or 21~~, ~~characterised in that~~ wherein the rollers ~~(71, 72)~~ are mounted and ~~preferably~~ arranged asymmetrically through one of sliding ~~or~~ and rolling bearings ~~(65)~~ on the passages ~~or~~ and with bearing bolts ~~(63, 64)~~ connected to the passages.
23. (Currently amended) The Ddrive system according to ~~at least one of the preceding~~ ~~claims~~ claim 1, ~~characterised in that~~ wherein the rollers ~~(71, 72)~~ have grooves ~~(73)~~ for guiding the radially flexible ring ~~(8)~~.
24. (Currently amended) The Ddrive system according to ~~at least one of the preceding~~ ~~claims~~ claim 1, ~~characterised in that~~ wherein circumferentially active damping elements ~~(56)~~ are integrated in the output hollow wheel ~~(5)~~.
25. (Currently amended) The Ddrive system according to ~~at least one of the preceding~~ ~~claims~~ claim 1, ~~characterised in that~~ wherein the output hollow wheel ~~(5)~~ is connected to a loop spring brake.
26. (Currently amended) The Ddrive system according to ~~at least one of the preceding~~ ~~claims~~ claim 1, ~~characterised in that~~ wherein the drive element ~~(10)~~ of the regulating device is connected in the axial direction to the output hollow wheel ~~(5)~~.

27. (Currently amended) The Ddrive system according to claim 26, ~~characterised in that~~ wherein holding clips (41) are integrated in the second housing cover (42) for axially fixing the drive element (10) of the regulating device.
28. (Currently amended) The Ddrive system according to ~~one of the preceding~~ claims 25 to 27, ~~characterised in that~~ wherein damping elements and/or a loop spring brake is/are mounted between the output hollow wheel (5) and the drive element (10).
29. (Currently amended) The Ddrive system according to ~~at least one of the preceding~~ ~~claims claim 1,~~ characterised in that wherein the output hollow wheel (5) is integrated in the drive element (15) of the regulating device.
30. (Currently amended) The Ddrive system according to ~~at least one of the preceding~~ ~~claims claim 1,~~ characterised in that wherein the output hollow wheel (5) is formed in one piece or in two pieces of plastics and a preferably metal bearing material, more particularly a sintered metal.
31. (Currently amended) The Ddrive system according to ~~at least one of the preceding~~ ~~claims 27 to 29,~~ characterised in that wherein a steel ring is mounted in the output hollow wheel to support the radial forces acting on the output hollow wheel.
32. (Currently amended) The Ddrive system according to ~~at least one of the preceding~~ ~~claims claim 1,~~ characterised in that wherein the radially flexible ring (8) has a supporting metal ring preferably of one of steel ~~or~~ and a steel alloy.
33. (Currently amended) The Ddrive system according to ~~at least one of the preceding~~ ~~claims claim 1,~~ characterised in that wherein the radially flexible ring (8) has a loop spring as supporting element.